

00/22/00  
01d

UTILITY PATENT APPLICATION TRANSMITTAL UNDER 37 C.F.R. §1.53(b)

ASSISTANT COMMISSIONER OF PATENTS

Box PATENT APPLICATION

Washington D.C. 20231

Case Docket No.: P-088

Sir:

Transmitted herewith for filing is the patent application of  
INVENTOR OR APPLICATION IDENTIFIER: Sang-Young NOH

FOR: REGISTER CONTROL APPARATUS FOR W-CDMA WLL SEPARATION TYPE TERMINAL

Enclosed are:

1. [X] 15 pages of specification, claims, abstract  
2. [X] 1 sheets of FORMAL drawing,  
3. [X] 2 pages of newly executed Declaration & Power of Attorney (original).  
4. [X] Priority Claimed.  
5. [ ] Small Entity Statement.  
6. [ ] Information Disclosure Statement, Form PTO-1449 and reference.  
7. [X] Assignment Papers for LG Information & Communications, Ltd.  
(cover sheet, assignment & assignment fee).  
8. [X] Certified copy of Korean Patent Application No. 42145/1999 filed September 30, 1999.  
9. [X] Two (2) return postcards.  
[X] Stamp & Return with Courier.  
[X] Prepaid Postcard-Stamped Filing Date & Returned with Unofficial Serial Number.  
10. [X] Authorization under 37 C.F.R. §1.136(a)(3).  
11. [ ] Other:

CLAIMS AS FILED

For	No. Filed		No. Extra	Rate	Fee
Total Claims	21	- 20	1	X \$18.00	\$18.00
Indep. Claims	3	- 3	0	X \$78.00	\$ 0.00
Multiple Dependent Claims (If applicable)				X \$260.00	\$ 0.00
				BASIC FEE	\$690.00
				TOTAL FILING FEE	\$708.00

- [ ] This is a Continuation-in-part (CIP) of prior application No: \_\_\_\_\_ filed \_\_\_\_\_. Incorporation By Reference-The entire disclosure of the prior application is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
- [ ] Amend the specification by inserting before the first line the sentence:  
-This application is a continuation-in-part of Application Serial No. \_\_\_\_\_ filed \_\_\_\_\_.-
- [X] A check in the amount of \$708.00 (Check # 8492) is attached.
- [ ] Please charge my Deposit Account No. 16-0607 in the amount of \$ \_\_\_\_\_. A duplicate copy of this sheet is enclosed.
- [X] The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 16-0607. A duplicate copy is enclosed.
- [X] Any additional filing fees required under 37 C.F.R. 1.16.
- [X] The Commissioner is hereby authorized to charge payment of following fees during the pendency of this application or credit any overpayment to Deposit Account No. 16-0607. A duplicate copy of this sheet is enclosed.
- [X] Any patent application processing fees under 37 C.F.R. 1.17.
- [X] Any filing fees under 37 C.F.R. 1.16 for presentation of extra claims.

FLESHNER & KIM, LLP

*[Signature]*  
Daniel Y.J. Kim  
Registration No. 36,186  
Stuart I. Smith  
Registration No. 42,159

Correspondence Address Below:

P.O. Box 221200  
Chantilly, VA 20153-1200  
(703) 502-9440

Date: March 22, 2000

U.S. PTO  
09/532952  
03/22/00

# REGISTER CONTROL APPARATUS FOR W-CDMA WLL SEPARATION TYPE TERMINAL

## **BACKGROUND OF THE INVENTION**

### **1. Field of the Invention**

The present invention relates to a wireless communication system, and more particularly to a register control apparatus for a separation type terminal in a wireless communication system.

### **2. Background of the Related Art**

Figure 1 is a block diagram illustrating a CDMA basic type terminal of the background technology. As shown therein, the background W-CDMA basic type terminal includes a microprocessor 11 for controlling operation of a system, a decoding logic unit 12 for decoding a control instruction of the microprocessor 11 and interpreting the decoded instruction signal, and a register 13 for storing data.

The above-described W-CDMA basic type terminal (decoding module 20) includes the decoding logic unit 12 and the register 13 in a module. In addition, there are further provided a modem module, a subscriber interface module, an RF module, etc., which are not shown in Figure 1.

Multiple modules 20 controlled by the microprocessor 11 are connected by a bus and are controlled by a chip select signal, a read signal and a write signal, which are control signals from the microprocessor 11.

5 The microprocessor 11 reads data stored in the register 13 of each module 20, checks the state of each module 20, writes data used for the next operation into the module register 13, and instructs the next operation of the module.

In the above-described operation, an address bus, a data bus, a chip select signal (CS), a write signal(WR) for writing data into a register, and a read signal(RD) for reading data from the register are used.

10 In the read operation, the microprocessor 11 generates an RD signal to the module 20 for reading data, and a particular module 20 is selected in accordance with the CS signal.

An address which will be read from among the addresses of the register 13 appears at the address bus, and the data read from the register appears at the data bus. At the same time, the data which appears at the data bus is read based on the generated RD signal.

15 In the write operation, the microprocessor 11 generates a WR signal to the module 20 for writing the data, and the module 20 is selected in accordance with the CS signal. An address which will be written among the addresses of the register 13 appears at the address bus, and the data which will be stored in the register 13 appears at the data bus. The data which appears at the data bus is written into the designated register.

However, in the background method, when the master unit and the slave unit are distanced by a few meters or hundreds of meters like the W-CDMA WLL separation type terminal, the above-described construction results in series problems such as: (1) it is impossible to transmit the address bus, data bus, CS signal, RD signal, and WR signal; and  
5 (2) when a new protocol is adapted between the master unit and the slave unit, a new microprocessor is needed in the slave unit for processing the protocol. In addition, in both cases the design of the system must be changed due to the decreased compatibilities with the software.

#### **SUMMARY OF THE INVENTION**

10 An object of the invention is to solve at least the above problems and/or disadvantages and to provide at least the advantages described hereinafter.

Accordingly, it is an object of the present invention to provide a register control apparatus between a master unit and a slave unit for a W-CDMA WLL separation type  
15 terminal which is capable of controlling two remote terminals by providing a transmission path between the master unit and the slave unit and sharing data between registers.

To achieve the above object and other objects, there is provided a register control apparatus between a master unit and a slave unit for a W-CDMA WLL separation type terminal which includes a mirror register of a master unit, a register of a slave unit, a framing logic unit for periodically transmitting and extracting data by the master unit and the slave unit through a time slot, and a transmission path for connecting the master unit and the slave unit.

To achieve further objects of the invention, there is provided a method of controlling a slave unit in a separation type terminal in a W-CDMA WLL system wherein data is transmitted between the master unit and the slave unit such that data contained in the master unit is the same as data contained in the slave unit, the slave unit is located remotely from the master unit, and the slave unit is controlled by the master unit based on data stored in the master unit and received from the slave unit.

Additional advantages, objects, and features of the invention will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the invention. The objects and advantages of the invention may be realized and attained as particularly pointed out in the appended claims.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

The invention will be described in detail with reference to the following drawings in which like reference numerals refer to like elements wherein:

Figure 1 is a block diagram illustrating a background W-CDMA WLL basic terminal;  
and

Figure 2 is a block diagram illustrating a register control apparatus between a master unit and a slave unit for a W-CDMA WLL according to the present invention.

### **DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS**

Figure 2 is a block diagram illustrating an example of a register control apparatus between a master unit 1 and a slave unit 2 for a W-CDMA WLL separation type terminal according to a preferred embodiment of the present invention. As shown therein, the register control apparatus includes a master unit 1, a slave unit 2, and a transmission path 25 connecting the master unit 1 and the slave unit 2.

The master unit 1 includes a microprocessor 21 for controlling the operations of the W-CDMA WLL separation type terminal, a decoding logic unit 22 for decoding control instructions of the microprocessor 21 and interpreting the decoded instruction signal, and a plurality of mirror registers 23 for storing the control instruction of the microprocessor 21 inputted through the decoding logic unit 22 and storing data of the slave unit 2. Also included in master unit 1 is a framing logic unit 24 for periodically transmitting the control instructions of the microprocessor 21 stored in the mirror registers 23 to the slave unit 2 through the transmission path 25 based on a time slot, receiving data of the slave unit 2 inputted through the transmission path 25, extracting the received data and storing the extracted data into the mirror registers 23.

The slave unit 2 includes a plurality of slave registers 26 for storing data and instructing the next instruction, and a framing logic unit 27 for periodically transmitting the data stored in the slave registers 26 to the master unit 1 through the transmission path 25 based on a time slot of the framing logic unit 27, receiving the contents of a mirror register 23 of the master unit 1 and storing the data extracted from the slave registers 26. The operation of slave unit 2 is controlled by the microprocessor 21. Namely, the slave unit 2 operates when the microprocessor 21 writes data into the slave registers 26.

Since the master unit and slave unit are remotely distanced, the transmission path 25 is used for periodically transmitting and receiving the data therebetween. The periodic transmission between the master unit and the slave unit through the allocated time slot is implemented by the framing logic units 24 and 27. The data of the mirror register 23 and the slave register 26 are changed during the above-described process, and the updated data is transmitted therebetween to maintain the same data state in both mirror register 23 and slave register 26.

In the write operation, the microprocessor 21 of the master unit 1 does not directly access the slave register 26 of the slave unit 2, but instead accesses the mirror register 23.

When data is written by the microprocessor 21 into a designated address of the mirror register 23, various buses of the microprocessor 21 write the data into the mirror registers 23 in a manner similar to the background method discussed above.

However, in the present invention, the data written in the mirror register 23 is periodically transmitted to the slave unit 2 through the time slot of the framing logic unit 24.

The transmitted data is extracted by the framing logic unit 27 of the slave unit 2 and is written into each slave register 26. The slave unit 2 operates based on the data written in the slave registers 26.

In the read operation, the data of the slave register 26 is periodically transmitted to the master unit 1 through an allocated time slot. In the master unit, the data is extracted from the time slot and is written into each mirror register 23. The microprocessor 21 of the master unit 1 reads the address stored in the mirror register 23 during the read operation in the same manner that the data written in a corresponding slave register 26 is read.

In the present invention, the transmission path 25 between the master unit 1 and the slave unit 2 can be implemented based on an E1(2.048Mbps) link. The states of the mirror registers 23 and the slave registers 26 are periodically transmitted to the corresponding opponents. Namely, in the case that the data of the slave register 26 of the slave unit 2 or the data of the mirror register 23 of the master unit 1 is changed, the changed contents are transmitted between the master unit 1 and the slave unit 2 at a period of 125  $\mu$ sec. In this way, the data of the mirror register 23 of the master unit 1 and the slave register 26 of the slave unit 2 are updated. The master unit 1 and the slave unit 2 of the W-CDMA WLL terminals periodically transmit and receive the data through the transmission path 25, extract the transmitted and received data, and store the data in a corresponding register. The



master unit 1 then accesses the mirror register 23 instead of the slave register 26 for controlling the slave unit 2.

In addition, the microprocessor 21 of the master unit accesses only the mirror register 23 through the bus, and the slave unit uses only the corresponding slave register 26. Even  
5 when two apparatuses are separated from each other, since the microprocessor accesses the mirror register existing at the same address, it is not necessary to change the address map and the protocol. In addition, complete design changes are not needed based on the hardware and software. As the amount of the data is increased, the capacity of the transmission path is increased for compatibility.

As described above, in the present invention, when control of the W-CDMA WLL  
10 separation type terminal and two remote apparatuses is needed, the control is implemented through a certain transmission path.

The foregoing embodiments and advantages are merely exemplary and are not to be construed as limiting the present invention. The present teaching can be readily applied  
15 to other types of apparatuses. The description of the present invention is intended to be illustrative, and not to limit the scope of the claims. Many alternatives, modifications, and variations will be apparent to those skilled in the art. In the claims, means-plus-function clauses are intended to cover the structures described herein as performing the recited function and not only structural equivalents but also equivalent structures.

**WHAT IS CLAIMED IS:**

1. A control apparatus for a separation type terminal having a master unit and a slave unit in a W-CDMA WLL system, the control apparatus comprising:

5 a mirror register local to the master unit and containing a mirror register data;  
a slave register local to the slave unit and containing a slave register data; and  
a transmission path,

wherein data is transmitted between the mirror register and the slave register  
through the transmission path so that the mirror register and the slave register data are the  
10 same.

2. The apparatus of claim 1, wherein the mirror register data and the slave  
register data are periodically transmitted and received.

15 3. The apparatus of claim 1, wherein the mirror register and the slave register are  
the same in type and capacity.

4. The apparatus of claim 1, further comprising:  
a master controller local to the master unit and containing a master framing  
20 unit; and  
a slave controller local to the slave unit and containing a slave framing unit,

wherein the transmission path connects the master controller to the slave controller and is a link obtained based on the amount of data processed by the slave controller.

5           5.     The apparatus of claim 1, further comprising:  
              a master frame logic unit local to the master unit;  
              a slave frame logic unit local to the slave unit,  
              wherein the data transmission and receiving operations between the mirror  
10           register and the slave register are performed periodically through a time slot allocated by  
              the master and slave frame logic units.

              6.     A control apparatus for a separation type terminal in a W-CDMA WLL  
              system, comprising:  
              a master unit having a mirror register;  
15           a slave unit having a slave register and controlled by the master unit; and  
              a transmission path for implementing a data transmission and receiving  
              operation between the master unit and the slave unit.

              7.     The apparatus of claim 6, wherein the master unit comprises:  
20           a microprocessor for controlling the W-CDMA WLL terminal;

a decoding logic unit for interpreting a control instruction of the microprocessor; and

a framing logic unit for transmitting data to and receiving data from the mirror register and the slave unit and storing the received data in the slave register.

5

8. The apparatus of claim 6, wherein the slave unit comprises:

a plurality of slave registers for storing data of the slave unit and storing data transmitted from the master unit; and

a framing logic unit for transmitting and receiving data between the mirror register and the slave unit, and for storing in one of the plurality of slave registers next operation data, state data of the slave unit, and received data.

10

9. The apparatus of claim 7, wherein the mirror register is formed of a register having a same capacity and type as the slave register.

15

10. The apparatus of claim 7, wherein the framing logic unit adjusts a frame synchronization of the master unit and the slave unit when transmitting the data using a certain clock signal as a sampling clock signal.

11. The apparatus of claim 7, wherein the framing logic unit periodically transmits a data of the mirror register to a framing logic unit of the slave unit through an allocated time slot.

5 12. The apparatus of claim 7, wherein the framing logic unit periodically receives slave register data through an allocated time slot and stores it in the mirror register.

13. The apparatus of claim 7, wherein the mirror register receives slave register data at a certain period and stores the same.

10 14. The apparatus of claim 8, wherein the framing logic unit periodically transmits slave register data to a framing logic unit of the master unit through an allocated time slot.

15 15. The apparatus of claim 8, wherein the framing logic unit periodically receives mirror register data through an allocated time slot and stores it in the slave register.

16. The apparatus of claim 7, wherein the framing logic unit periodically performs a data transmission through a framing logic unit of the slave unit and the transmission path.

17. The apparatus of claim 8, wherein the framing logic unit periodically performs a data transmitting and receiving operation through a framing unit of the master unit and the transmission path.

5 18. The apparatus of claim 6, wherein the transmission path is a transmission link formed based on the amount of data processed by the slave unit and has a connection structure between the slave unit and the master unit.

10 19. The apparatus of claim 6, wherein the mirror register contains data that is the same as data contained by the slave register, and the master unit uses the mirror register to control the slave unit.

15 20. A method of controlling a slave unit in a separation type terminal in a W-CDMA WLL system, the method comprising:

transmitting data between a master unit and the slave unit such that data contained in the master unit is a duplicate of data contained in the slave unit, the slave unit being located remotely from the master unit; and

controlling the slave unit with the master unit based on data stored in the master unit and received from the slave unit.

21. The method of claim 20, wherein the data is periodically transmitted and received by the master unit and the slave unit.

### **ABSTRACT OF THE DISCLOSURE**

A register control apparatus is provided between a master unit and a slave unit for a W-CDMA WLL separation type terminal which includes a mirror register of a master unit,  
5 a register of a slave unit, a framing logic unit for periodically transmitting data to and extracting data from the master unit and the slave unit through a time slot, and a transmission path for connecting the master unit and the slave unit.



FIG. 1  
BACKGROUND ART





FIG. 2



**DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that:

My residence, post office and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter claimed and for which a patent is sought on the invention entitled REGISTER CONTROL APPARATUS FOR W-CDMA WLL SEPARATION TYPE TERMINAL, the specification of which

☒ [ X ] is attached hereto ☐ [ ] was filed on \_\_\_\_\_ as Application Serial No. \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is known to me to be material to patentability in accordance with Title 37, Code of Federal Regulations, Section 1.56(a).

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365 (b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

**Prior Foreign Application(s):****Number****Country****Foreign Filing Date****Month/Day/Year**42145/1999Korea09/30/99

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

**Application Number(s):****Filing Date (Month/Day/Year)**

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

**Prior U. S. Application  
or PCT Parent Number****Filing Date (Month/Day/Year)****Parent Patent Number (if applicable)**

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint the following attorney(s) and/or agent(s): Daniel Y.J. Kim, Registration No. 36,186 and Mark L. Fleshner, Registration No. 34,596; Carl R. Wesolowski, Registration No. 40,372, John C. Eisenhart, Registration No. 38,128, Rene A. Vazquez, Registration No. 38,647; Michael J. Cornelison, Registration No. 40,395; Stuart I. Smith, Registration No. 42,159; and Carol L. Druzbeck, Registration No. 40,287, all of

FLESHNER & KIM, LLP  
P. O. Box 221200  
Chantilly, Virginia 20153-1200

with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and all future correspondence should be addressed to them.

Full name of sole or first inventor: Sang-Young NOH

Inventor's signature: Sang-Young Noh

Date: MAR. 10, 2000

Residence: Kyungki-Do, Korea

Citizenship: Republic of Korea

Post Office Address: Jukong Apt. 108-411, 849, Kumjung-Dong, Kunpo, Kyungki-Do, Korea

Full name of joint inventor(s):

Inventor's signature:

Date:

Residence:

Citizenship:

Post Office Address:

Full name of joint inventor(s):

Inventor's signature:

Date:

Residence:

Citizenship:

Post Office Address: